

MOTIP Hammerfinish Paint

Technical Information



Fast-drying paint with hammered effect for treated and untreated surfaces including wood, metal, aluminium, glass and plastic. MOTIP Hammerfinish Paint offers good coverage, is shock proof and is resistant to scratches, petrol, chemicals, thinned cleaners and weather influences.

Ord.-no: 04011, 04012, 04013, 04014, 04015, 04017

Quality & properties

Fast drying
Good coverage
Scratch free and shock proof
Resistant to petrol, chemicals, thinned cleaners and weather influences

Physical & chemical data

Base: Alkyd resin
Colourname:

- blue
- green
- silver
- grey
- gold
- anthracite

Smell: Characteristic
Degree of gloss: gloss, >75
Efficiency: 400 ML – 1.25 - 1.75 m²
Dust dry: 5 - 10 min
Dry to touch: 10 - 20 min
Completely dry: 24 h
Overcoatable: 24 h
Surfaces: Wood, metal, aluminium, glass, stone and various types of plastic.
Minimum Working Temperature: 10 °C
Maximum Working Temperature: 25 °C
Flash point: n.a.
Temperature resistance: 110 °C
Storage stability:

- 10 m
- 10 years

Content: 400 ML

How to use

Before use, carefully read the directions on the packaging and act accordingly.

Pre Treatment: The surface should be clean, dry and free of grease. Remove loose old lacquer and rust and sand the surface. Apply a layer of MOTIP primer suitable for the surface. After drying, sand the base layer (grain 600).

Treatment: The surface should be clean, dry and free of grease. The aerosol should have room temperature. Best processing temperature 10 to 25°C.

Before use, shake the aerosol for 2 minutes and spray a sample. Distance to the surface to be treated approximately 25 to 30 centimetre.

Apply a thin first layer and after several minutes apply a finishing coat. Before applying the next layer, again shake the aerosol.

After use, clean the valve (turn aerosol upside down and press the nozzle for approximately 5 seconds).

The drying time depends on the ambient temperature, the humidity of the air and the thickness of the lacquer applied.

Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

As of August 4, 2025 – This release replaces all eventually earlier issued versions.