



PRODUCT NUMBER: 1005605
**Honeywell 4110 ML - FFP1 NR
D**

Honeywell

Overview

Reference Number

1005605

Product Type

Respiratory Protection

Range

Disposable APR

Line

Folding masks

Brand

Honeywell

Brand formerly known as

WILLSON

Industry

- Industry
- Building and Construction
- Iron and steel industry
- Textile Industries

Product Use

Application: Textile, construction, iron and steel industries, etc ... Protects against dusts, mists and fumes containing calcium carbonate, clay, kaolin, cellulose, cotton, flour, ferrous metals, vegetal and mineral oils, metal-working fluids (this list is non-exhaustive).

Maximum usage level: can be used in atmospheres containing solid and/or liquid aerosols in concentrations up to 4 x WEL*: FFP1 class (low toxicity). "NR" (Non Reusable) marked, it can be used one single shift (according to EN 149:2001+A1:2009). Certain restrictions or limitations may apply in the case of specific contaminants. Please refer to applicable health and safety standards.

Limitation to use:

This single-use filtering half-mask should NOT be used in the following situations :

- oxygen concentration is less than 17% (oxygen-deficient atmospheres)
- contaminants or their concentrations are unknown or are immediately dangerous to life or health
- contaminants concentrations exceed levels fixed by applicable health and safety standards or 4 x WEL*
- in the presence of toxic or radio-active contaminants
- in the presence of gases or vapours
- fire fighting.

Caution:

We recommend users to ensure that the level of protection offered by the respirator is sufficient for the type and

concentration of contaminant(s) in the work area.

For use only by trained and qualified personnel.

Leak-tightness is unlikely to be achieved if the mask is worn against a beard or facial stubble.

This respirator does not supply oxygen.

* WEL: Workplace exposure Limit.

Features & Benefits

Feature

Individually packed folding respirator made of an ultra-soft hypoallergenic flange seal Willtech with absorption properties and a tight film. Nose-bridge Colour-coded. Vast interior volume with built-in chin piece. Ultra-light (7 g). Fluid-resistant outer shell. Sliding straps, highly flexible and resistant. No latex, PVC or Silicone. Box dispenser. Dolomite tested.

Benefit

Easy storage and transport (in the pocket). Exceptional comfort. Prevents irritation and allergies. Better wearer acceptance with regard to duration. Reduces risks of contamination. Increases safety (no risk of leakages due to staples) and saves time. No restrictions with regard to use. Environment concerned.

Technical Description

Standard

EN149:2001

Mask Type

Flat Fold

Protection Class

FFP1

Valve

No

Straps

Single elastic

Mask Size

Medium

Latex Free

Yes

PVC Free

Yes

Silicone Free

Yes

Certifications

EC Category PPE

3

Quality Assurance

ISO 9001 / 2000

EC Certificate Number

0082/236/079/04/19/0493

EC Attestation

0082/236/079/04/19/0493

EC Attestation Number

0082/236/079/04/19/0493

Certifications

- EN 149:2001 + A1:2009

Literature & Documents

9100009-01_4000series_29L_HonNorth

http://www.honeywellsafety.com/supplementary/documents_and_downloads/secured/respiratory_protection/4295003423/1033.aspx

Maintenance

Life Cycle

5 years

Storage Information

Temperature range of storage conditions: -20°C/+40°C

Maximum relative humidity of storage conditions: less than 95%

Packaging

Quantity per Box/Pack/Case

1, 20, 200