

New



Low-profile forward/reverse control

Durable composite housing

Power regulator

Nickel-plated head
provides enhanced corrosion resistance

Variable speed lever
for superior control

Rear exhaust
directing air away from the operator and workplace

With the 1105MAX Series air ratchets, you get best-in-class power and speed coupled with superior features to give you MAX Power, MAX Control, and MAX Comfort.

MAX Power

41 Nm (30 ft-lb) of maximum torque combined with 300 rpm deliver best-in-class power for most difficult fasteners with the speed to get the job done even faster.

MAX Control

Variable speed lever and easily accessible power regulator allow easy and precise power control.

MAX Comfort

Ergonomic design improves operator comfort and composite handle insulates from cold.

Specifications at 6.2 bar (90 PSI)

Part number	1105MAX-D2
Ordering number	45649035
Drive size (square)	1/4 in
Also available with 3/8" square drive:	1105MAX-D3

PERFORMANCE

Working torque	5 - 25 ft-lb / 7 - 34 Nm
Maximum torque	30 ft-lb / 41 Nm
Recommended fastener size	3/8 in / M10
Free speed	300 rpm

AIR SYSTEM

Air inlet (NPTF)	1/4 in
Minimum hose size	3/8 in / 10 mm
Average air consumption	3.5 cfm / 99 l/min
Air consumption at free speed	20 cfm / 566 l/min

NOISE & VIBRATIONS

Sound pressure / power (ISO15744)	88.9 / 99.9 dB(A)
Vibration level / measurement uncertainty (ISO28927)	5.7 / 1.0 m/s²

WEIGHT & DIMENSIONS

Tool weight	1.43 lb / 0.65 kg
Tool length	7.36 in / 187 mm
Head dimensions (w x h)	0.79 x 0.79 in / 20 x 20 mm
Shipping weight	1.75 lb / 0.79 kg
Shipping dimensions (l x w x h)	220 x 65 x 55 mm
UPC/EAN Code	6 63023 07704 8

