

## HANDWELD 15 THT

P702KHC

Protection from heat  
MIG-MAG Welding

### Benefits

- Excellent tear and abrasion resistance (Level 4): longer service life
- Kevlar® seams
- Forearm protection
- Comfort: fleecy cotton lining
- Heat-resistant leather: resistance to high temperatures

### Applications

- MIG/MAG welding
- Heavy-duty handling of hot parts

### Packaging

- Set of 10 pairs
- Box of 50 pairs

Sizes	Skus numbers
T9	64 081 403
T10	43 047 078

Sizes	Skus numbers
T11	64 081 519
T12	64 081 527*

\*Not on stock - made to order



By purchasing this product, you are supporting responsible leather manufacturing through LWG. [www.leatherworkinggroup.com](http://www.leatherworkinggroup.com)



### Description

- Five-finger gunn cut pattern glove
- Orange, heat-resistant, cow split leather covering palm and index finger
- Inside fleecy cotton lining
- 15-cm, split buffalo leather gauntlet cuff
- Kevlar® seams
- Excellent abrasion, tear and puncture resistance
- Resistant to contact heat (up to 100°C)
- Excellent resistance to flammability and small splashes of molten metal

Category II glove: protection against mechanical risks and thermal hazards

### Composition

- Material: Orange/natural-coloured split cow leather
- Length: 35 cm
- Leather thickness: 1.2 to 1.4 mm (glove) and 1.1 to 1.4 mm (gauntlet cuff)

### Standards



Abrasion resistance	4/4
Cut resistance (coup test)	1/5
Tear resistance	4/4
Puncture resistance	4/4
Cut resistance (TDM test)	X/F



Limited flame spread	4/4
Contact heat	1/4
Convective heat	2/4
Radiant heat	1/4
Small splashes of molten metal	4/4
Large splashes of molten metal	X/4

"X" means that the test has not been performed

EN12477:2001/A1:2005 Type A

EN ISO 21420