



PRODUCT NUMBER: 1007221
**Honeywell 5185 ML - FFP1 NR
D**

Honeywell

Overview

Reference Number

1007221

Product Type

Respiratory Protection

Range

Disposable APR

Line

Moulded masks

Brand

Honeywell

Brand formerly known as

WILLSON

Industry

- Building and Construction
- Iron and steel industry
- Textile Industries

Product Use

Application: Textile, construction, iron and steel industries, etc ... Protects against dusts, mists and fumes containing calcium carbonate, clay, kaolin, cellulose, cotton, flour, ferrous metals, vegetal and mineral oils, metal-working fluids (*this list is non-exhaustive*).

Maximum usage level: can be used in atmospheres containing solid and/or liquid aerosols in concentrations up to 4 x WEL*: FFP1 class (low toxicity). "NR" (Non Reusable) marked, it can be used one single shift (according to EN 149:2001+A1:2009) . Certain restrictions or limitations may apply in the case of specific contaminants. Please refer to applicable health and safety standards.

Limitation to use:

This single-use filtering half-mask should NOT be used in the following situations :

- oxygen concentration is less than 17%
- contaminants or their concentrations are unknown or are immediately dangerous to life or health
- contaminants concentrations exceed levels fixed by applicable health and safety standards or 4 x WEL*
- in the presence of toxic or radio-active contaminants
- in the presence of gases or vapours
- fire fighting.

Caution:

We recommend users to ensure that the level of protection offered by the respirator is sufficient for the type and concentration of contaminant(s) in the work area.

For use only by trained and qualified personnel.

Leak-tightness is unlikely to be achieved if the mask is worn against a beard or facial stubble.

This respirator does not supply oxygen.

* WEL : Workplace Exposure Limit.

Features & Benefits

Feature

Rigid shell for a shape maintained even in moistened and heavy loading environments. Pre-formed and coloured nosebridge for a better fit and an instant identification of the protection level of the respirator. Large internal volume for a better comfort and an easier communication. Twin elastic straps, ultra flexible and strong, stapled outside the filtering area to avoid any risk of leakages. Lightweight respirator (10 g) for a better wearer acceptance with regard to duration. No latex, no silicone, no PVC.

Benefit

Increased safety and improved comfort, whatever the environment and duration of use. Optimised wearer acceptance. Time saved to adjust the respirator and identify its protection level. No risk of allergy or environment respect.

Technical Description

Standard

EN149:2001

Mask Type

Molded Cup

Protection Class

FFP1

Valve

No

Straps

Double elastics

Mask Size

Medium

Latex Free

Yes

PVC Free

Yes

Silicone Free

Yes

Certifications

EC Category PPE

3

Quality Assurance

ISO 9001 / 2000

EC Certificate Number

0082/236/079/10/19/1066

EC Attestation

0082/236/079/10/19/1066

EC Attestation Number

0082/236/079/10/19/1066

Certifications

- EN 149:2001 A1:2009

Literature & Documents

90025791-01_5000series_29L_EAC_HonNorth

http://www.honeywellsafety.com/supplementary/documents_and_downloads/secured/respiratory_protection/4295003425/1033.aspx

Maintenance

Life Cycle

3 years

Storage Information

Temperature range of storage conditions: -20°C/+40°C

Maximum relative humidity of storage conditions: less than 95%

Packaging

Quantity per Box/Pack/Case

20, 200, 5 400