

MOTIP Plastic Primer

Technical Information



MOTIP Plastic Primer to treat untreated surfaces of various types of plastic. MOTIP Plastic Primer offers excellent adhesion, does not require sanding and can be resprayed with all paints.

Ord.-no: 04063, 880103

Quality & properties

Fast drying
Excellent adhesion
Re-sprayable with all lacquer systems
Not suitable for treatment of PE

Physical & chemical data

Base: Polyolefin resin
Colourname: no colour
Smell: Characteristic
Degree of gloss: mat, 10 ±2
Efficiency:

- 400 ML – 2.0 - 3.0 m²
- 150 ML – 0.75 -1.2 m²

Dust dry: 10 min
Completely dry: 10 - 15 min
Overcoatable: 10 - 15 min
Surfaces:

- Several types of plastic.
- car parts, garden furniture and other objects of coatable hard plastics

Minimum Working Temperature: 10 °C
Maximum Working Temperature: 25 °C
Flash point:

- n.a.
- n.a. °C

Temperature resistance: 110 °C
Storage stability: 10 years
Content:

- 400 ML
- 150 ML

How to use

Before use, carefully read the directions on the packaging and act accordingly.

Pre Treatment: The surface should be clean, dry and free of grease. When desired, slightly sand the surface, grain 600.

Treatment: The surface should be clean, dry and free of grease. The aerosol should have room temperature. Best processing temperature 10 to 25°C.

Before use, shake the aerosol for 2 minutes and spray a sample. Distance to the surface to be treated approximately 25 to 30 centimetre.

Apply the plastic primer in maximum two (2) thin layers. After drying, without sanding, re-sprayable with all lacquer systems.

After use, clean the valve (turn aerosol upside down and press the nozzle for approximately 5 seconds).

The drying time depends on the ambient temperature, the humidity of the air and the thickness of the lacquer applied.

Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

As of August 4, 2025 – This release replaces all eventually earlier issued versions.