

TECHNICAL SPECIFICATION

EYE PROTECTION



EVOGuard™ C1 Industrial Visor

EVOGuard™ C1 Industrial Visor / Code: ADA240-060-000



SAFETY STANDARDS

EN 166

EN 170

SPECIFICATIONS



ULTRAVIOLET FILTER SCALE NUMBER
2C-1.2



MANUFACTURERS TRADEMARK
JSP Dagger



OPTICAL QUALITY (1=HIGH, 3=LOW)
1



MEDIUM ENERGY IMPACT 120 M/S
B when fitted to an EVO Helmet



MEDIUM ENERGY IMPACT 120 M/S
B When Fitted to EVOGuard Browguard



FOR PROTECTION AT EXTREMES OF TEMPERATURE
T



RESISTANCE TO LIQUID DROPLETS
3



BSI KITEMARK
Yes

MATERIAL
Polycarbonate Shield



PRODUCT WEIGHT
185g



RECYCLABLE
Yes



KIT
Supplied With: EVO 2,3,5,DS, Lite, Skyworker Arms.
EVO8/EVOLite Badgholder Arms. EVOGuard
Browguard Mounting System

FEATURES



Compatibility

EVOGuard™ visors maximise compatibility with JSP half masks, disposable respirators, prescription glasses and the Sonis® helmet mounted ear defender range.



Vision

The optical class 1 visor offers a panoramic view with minimal distortion, ideal for comfortable all day wear.



Impact

Five high performance visors offering up to A rated impact resistance when fitted to a safety helmet and fully compatible with EVOGuard™ browguard for medium energy impact protection.



Coverage

EVOGuard™ visors provide comprehensive facial coverage without limiting movement. EVOGuard™ MAX visors offer enhanced coverage with an integral chinguard.



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.
Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jsspsafety.com / Web: www.jsspsafety.com
Do Not Publish without written permission from JSP Limited. Contact copyright@jsspsafety.com.
Information correct in the United Kingdom at date of issue and may be subject to change.
Issued 1 Jun 2020 / Copyright 2018 - 2020. JSP Limited. All Rights Reserved.

