

AIR'FIT FFP2 NR D

58 224 286 (unvalved)

58 224 294 (valved)

FFP2 NR D



APPLICATION

Protection against toxic particles and solid and/or liquid aerosols marked as hazardous or as an irritant: dusts from: concrete, kaolin, epoxy resins, wood (except for beech and oak), iron, zinc oxide and nickel dusts, and welding fumes and influenza A viruses.

BONUS | Filters out 94 % of dust
(mean diameter: 0.6 microns)

Main features

Filtering media: Polypropylene

Elastic strap: Synthetic latex

Valve body: Polypropylene

Valve membrane: Vulcanised rubber

WEL*: 10 times the WEL

Maximum duration of use: 8 hours during a single period of work

NR marking: Not Reusable

Shelf-life: 5 years starting from the date of manufacture (under satisfactory storage conditions):

- Maximum relative humidity: 90 %

- Storage temperature between -20°C and +40° C

Do not use: If oxygen level is < 17 % or in the assumed or potential presence of toxic gases.

*WEL: Workplace exposure limit.

The average concentration, during an 8-hour working day and a 40-hour working week, at which the daily exposure does not endanger the individual's health.

Description

- Cup-shaped, non reusable, filtering half mask for protection against particles.
- Extremely fine and light filtering media for wear comfort even over long periods.
- Elastic band (no staples) for easy adjustment.
- Sealed tabs (no staples and no additional plastic parts).
- Ribbed cup for easy grip, preformed nose.
- Lightweight and comfortable.
- One size fits all.
- Made in Europe.

Available in 2 versions:

• **Unvalved:** 58 224 286

• **Valved:** 58 224 294 for greater respiratory comfort and no fogging for persons wearing glasses.

Valve colour coding for quick identification of the protection level.

Standards

- EN 149: 2001 + A1: 2009

Tests

- 120 mg loading test (as per the requirements of amendment A1: 2006 of standard 143: 2000).
- Tested using dolomite dust (resistance to clogging and longer service life in high dust environments).
- This test is an optional requirement of standard EN 149.

Packaging

- Box of 10 masks
- Carton of 12 boxes