

PISTOOL EN PU-SCHUIMREINIGER**1. Identificatie van de stof/preparaat en van de vennootschap/onderneming****1.1 Identificatie van de stof of het preparaat:**

- Niet van toepassing

1.2 Gebruik van de stof of het preparaat:

Reiniger

1.3 Identificatie van de vennootschap/onderneming:

SOUDAL N.V.
Everdongenlaan 18-20
B-2300 Turnhout
Tel. : +32 14 42 42 31
Fax : +32 14 44 39 71

1.4 Telefoonnummer voor noodgevallen:

+32 14 58 45 45
Brandweerinformatiecentrum voor gevaarlijke stoffen (B.I.G.)
Technische Schoolstraat 43 A, B-2440 Geel

2. Samenstelling en informatie over de bestanddelen

Gevaarlijke bestanddelen	CAS-nr. EINECS-nr.	Conc in %	Gevaars- symbool	Risico's (R-zinnen)
aceton	67-64-1 200-662-2	> 25	F+Xi	11-36-66-67 (1)
butaan	106-97-8 203-448-7	10 - 20	F+	12 (1)
isobutaan	75-28-5 200-857-2		F+	12 (1)
propaan	74-98-6 200-827-9	10 - 20	F+	12 (1)

(1) Voor volledige tekst van R-zinnen: zie rubriek 16

3. Identificatie van de gevaren

- Zeer licht ontvlambaar
- Irriterend voor de ogen
- Herhaalde blootstelling kan een droge of een gebarsten huid veroorzaken
- Dampen kunnen slaperigheid en duizeligheid veroorzaken

Afdrukdatum
Opgesteld door

: 11-2005
: Brandweerinformatiecentrum voor Gevaarlijke Stoffen vzw (BIG)
Technische Schoolstraat 43 A, B-2440 Geel
☎ +32 14 58 45 47

<http://www.big.be>

E-mail: info@big.be

1/10

MSDS gemaakt op
Referentienummer
Reden van revisie

: 11-05-2002
: BIG\33075NL
: Zie rubriek 13

Revisiedatum
Revisienummer

: 25-06-2005
: 005

4. Eerstehulpmaatregelen

- 4.1 Contact met de ogen:**
- Onmiddellijk met veel water spoelen
 - Arts raadplegen
- 4.2 Contact met de huid:**
- Onmiddellijk met veel water spoelen
 - Bij blijvende irritatie: arts raadplegen
- 4.3 Na inademen:**
- Breng het slachtoffer in de frisse lucht
 - Arts raadplegen
- 4.4 Na inslikken:**
- Nooit water toedienen indien slachtoffer bewusteloos is
 - Niet laten braken
 - Arts raadplegen

5. Brandbestrijdingsmaatregelen

- 5.1 Geschikte blusmiddelen:**
- Verneveld water
 - BC-poeder
 - Zand/aarde
- 5.2 Te mijden blusmiddelen:**
- Geen
- 5.3 Speciaal blootstellingsgevaar:**
- Bij verbranding: vorming van koolstofmonoxide en koolstofdioxide
 - Verspreiden van gas/damp langs de grond: ontstekingskans
 - Spuitbus kan exploderen o.i.v. warmte
- 5.4 Instructies:**
- Rekening houden met toxisch bluswater
 - Bluswater beperken, zo mogelijk opvangen of indammen
 - Lading niet verplaatsen indien aan hitte blootgesteld
- 5.5 Speciale beschermende uitrusting voor brandweerlieden:**
- Bij verhitting/verbranding: perslucht-/zuurstoftoestel

6. Maatregelen bij accidenteel vrijkomen van de stof of het preparaat

- 6.1 Persoonlijke beschermingsmiddelen/voorzorgsmaatregelen:**
- Zie rubriek 8.1/8.3/10.3
- 6.2 Milieuvoorzorgsmaatregelen:**
- Passende maatregelen nemen om verspreiding in het milieu te voorkomen
- 6.3 Opruiming/reinigingsmethoden:**
- Morsvloeistof absorberen in inert absorptiemiddel o.a.: zand/aarde
 - Verzameld product overdragen aan producent/bevoegde dienst
 - Na werkzaamheden kleding en materiaal reinigen

7. Hantering en opslag

- 7.1 Hantering:**
- Normale hygiëne
 - Bij ontoereikende ventilatie: open vuur en vonken vermijden
 - Verontreinigde kleding reinigen

PISTOOL EN PU-SCHUIMREINIGER

7.2 Opslag:

- Beschermen tegen directe zonnestralen
- Verwijderd van: warmtebronnen, ontstekingsbronnen, oxidatiemiddelen, zuren, basen

Opslagtemperatuur	: < 50	°C
Maximum hoeveelheid	: N.B.	kg
Maximum stockeertijd	: 365	dagen
Materiaalkeuze verpakking	:	
- geschikt	: aërosolverpakking	

7.3 Specifieke toepassingen:

- Zie de aanwijzingen van de fabrikant

8. Maatregelen ter beheersing van blootstelling/persoonlijke bescherming

8.1 Grenswaarden voor blootstelling:

ACETON:

TLV-TWA	: -	mg/m ³	500	ppm
TLV-STEL	: -	mg/m ³	750	ppm
TLV-Ceiling	: -	mg/m ³	-	ppm
OES-LTEL	: 1810	mg/m ³	750	ppm
OES-STEL	: 3620	mg/m ³	1500	ppm
MAK	: 1200	mg/m ³	500	ppm
TRK	: -	mg/m ³	-	ppm
MAC-TGG 8 u	: 1780	mg/m ³		
MAC-TGG 15 min.	: -	mg/m ³		
MAC-Ceiling	: -	mg/m ³		
VME-8 u	: 1800	mg/m ³	750	ppm
VLE-15 min.	: -	mg/m ³	-	ppm
GWBB-8 u	: 1806	mg/m ³	750	ppm
GWK-15 min.	: 2415	mg/m ³	1000	ppm
Momentane waarde	: -	mg/m ³	-	ppm
EG	: 1210	mg/m ³	500	ppm
EG-STEL	: -	mg/m ³	-	ppm

BUTAAN:

TLV-TWA	: -	mg/m ³	800	ppm
TLV-STEL	: -	mg/m ³	-	ppm
TLV-Ceiling	: -	mg/m ³	-	ppm
OES-LTEL	: 1450	mg/m ³	600	ppm
OES-STEL	: 1810	mg/m ³	750	ppm
MAK	: 2400	mg/m ³	1000	ppm
TRK	: -	mg/m ³	-	ppm
MAC-TGG 8 u	: 1430	mg/m ³		
MAC-TGG 15 min.	: -	mg/m ³		
MAC-Ceiling	: -	mg/m ³		
VME-8 u	: 1900	mg/m ³	800	ppm
VLE-15 min.	: -	mg/m ³	-	ppm
GWBB-8 u	: 1928	mg/m ³	800	ppm
GWK-15 min.	: -	mg/m ³	-	ppm
Momentane waarde	: -	mg/m ³	-	ppm
EG	: -	mg/m ³	-	ppm
EG-STEL	: -	mg/m ³	-	ppm

PISTOOL EN PU-SCHUIMREINIGER

ISOBUTAAN:

TLV-TWA	: -	mg/m ³	-	ppm
TLV-STEL	: -	mg/m ³	-	ppm
TLV-Ceiling	: -	mg/m ³	-	ppm
OES-LTEL	: -	mg/m ³	-	ppm
OES-STEL	: -	mg/m ³	-	ppm
MAK	: 2400	mg/m ³	1000	ppm
TRK	: -	mg/m ³	-	ppm
MAC-TGG 8 u	: -	mg/m ³		
MAC-TGG 15 min.	: -	mg/m ³		
MAC-Ceiling	: -	mg/m ³		
VME-8 u	: -	mg/m ³	-	ppm
VLE-15 min.	: -	mg/m ³	-	ppm
GWBB-8 u	: -	mg/m ³	-	ppm
GWK-15 min.	: -	mg/m ³	-	ppm
Momentane waarde	: -	mg/m ³	-	ppm
EG	: -	mg/m ³	-	ppm
EG-STEL	: -	mg/m ³	-	ppm

PROPAAN:

TLV-TWA	: -	mg/m ³	2500	ppm
TLV-STEL	: -	mg/m ³	-	ppm
TLV-Ceiling	: -	mg/m ³	-	ppm
OES-LTEL	: -	mg/m ³	-	ppm
OES-STEL	: -	mg/m ³	-	ppm
MAK	: 1800	mg/m ³	1000	ppm
TRK	: -	mg/m ³	-	ppm
MAC-TGG 8 u	: -	mg/m ³		
MAC-TGG 15 min.	: -	mg/m ³		
MAC-Ceiling	: -	mg/m ³		
VME-8 u	: -	mg/m ³	-	ppm
VLE-15 min.	: -	mg/m ³	-	ppm
GWBB-8 u	: -	mg/m ³	-	ppm
GWK-15 min.	: -	mg/m ³	-	ppm
Momentane waarde	: -	mg/m ³	-	ppm
EG	: -	mg/m ³	-	ppm
EG-STEL	: -	mg/m ³	-	ppm

8.2 Maatregelen ter beheersing van blootstelling:

8.2.1 Beheersing van beroepsmatige blootstelling:

- Uitsluitend op goed geventileerde plaatsen gebruiken

8.2.2 Beheersing van milieublootstelling: zie rubriek 13

8.3 Persoonlijke beschermingsmiddelen:

8.3.1 adembescherming:

- Bij ontoereikende ventilatie: adembescherming met filtertype A

8.3.2 handbescherming:

- Chemisch bestendige handschoenen

8.3.3 oogbescherming:

- Veiligheidsbril

8.3.4 huidbescherming:

- Geschikte beschermkleding

PISTOOL EN PU-SCHUIMREINIGER

9. Fysische en chemische eigenschappen

9.1 Algemene informatie:

Voorkomen (bij 20°C)	: Aërosol
Geur	: Aceton
Kleur	: Kleurloos

9.2 Belangrijke informatie met betrekking tot de gezondheid, de veiligheid en het milieu:

pH-waarde	: N.B.	
Kookpunt/kooktraject	: N.B.	°C
Vlampunt	: Bevat (zeer) licht ontvlambare componenten	
Explosiegrenzen	: 1.5 - 12.8	Vol%
Dampdruk (bij 20°C)	: N.B.	hPa
Dampdruk (bij 50°C)	: N.B.	hPa
Relatieve dichtheid (bij 20°C)	: N.B.	
Wateroplosbaarheid	: N.B.	g/100 ml
Oplosbaar in	: ethanol, ether	
Relatieve dampdichtheid	: N.B.	
Viscositeit (bij 20°C)	: N.B.	Pa.s
Verdelingscoëfficiënt n-octanol/water	: N.B.	
Verdampingssnelheid		
t.o.v. butylacetaat	: N.B.	
t.o.v. ether	: N.B.	

9.3 Andere gegevens:

Smeltpunt/smelttraject	: N.B.	°C
Zelfontbrandingstemperatuur	: N.B.	°C
Verzadigingsconcentratie	: N.B.	g/m ³

10. Stabiliteit en reactiviteit

10.1 Te vermijden omstandigheden/chemische reacties:

- Niet stabiel o.i.v. warmte

10.2 Te vermijden stoffen:

- Verwijderd van: warmtebronnen, ontstekingsbronnen, oxidatiemiddelen, zuren, basen

10.3 Gevaarlijke ontledingsproducten:

- Bij verbranding: vorming van koolstofmonoxide en koolstofdioxide

11. Toxicologische informatie

11.1 Acute toxiciteit:

ACETON:

LD50 oraal rat	: 5800	mg/kg
LD50 dermaal rat	: 20000	mg/kg
LD50 dermaal konijn	: N.B.	mg/kg
LC50 inhalatie rat	: 71	mg/l/4 u
LC50 inhalatie rat	: 30000	ppm/4 u

BUTAAN en ISOBUTAAN:

LD50 oraal rat	: N.B.	mg/kg
LD50 dermaal rat	: N.B.	mg/kg
LD50 dermaal konijn	: N.B.	mg/kg
LC50 inhalatie rat	: 658	mg/l/4 u
LC50 inhalatie rat	: N.B.	ppm/4 u

PROPAAN:

LD50	oraal rat	:	N.B.	mg/kg
LD50	dermaal rat	:	N.B.	mg/kg
LD50	dermaal konijn	:	N.B.	mg/kg
LC50	inhalatie rat	:	513	mg/l/4 u
LC50	inhalatie rat	:	280000	ppm/4 u

11.2 Chronische toxiciteit:

ACETON:

EG-carc. cat. : niet opgenomen
EG-muta. cat. : niet opgenomen
EG-repr. cat. : niet opgenomen

Kankerverwekkend (TLV) : A4
Kankerverwekkend (MAC) : niet opgenomen
Kankerverwekkend (VME) : niet opgenomen
Kankerverwekkend (GWBB) : niet opgenomen

Kankerverwekkend (MAK) : niet opgenomen
Mutageniteit (MAK) : niet opgenomen
Teratogeniteit (MAK) : Groep -

IARC-classificatie : niet opgenomen

11.3 Wijze van blootstelling: inademen, ogen en huid

11.4 Acute effecten/symptomen (bij overmatige blootstelling):

NA INADEMEN:

BIJ BLOOTSTELLING AAN HOGE CONCENTRATIES:

- Zwaktegevoel
- Depressie centraal zenuwstelsel
- Duizeligheid
- Bedwelming
- Opgewonden/rusteloos
- Dronken gevoel
- Gestoord reactievermogen
- Hoofdpijn
- Ademhalingsmoeilijkheden
- Bewustzijnsstoornissen

NA CONTACT MET DE OGEN:

- Irritatie van het oogweefsel

NA CONTACT MET DE HUID:

NA LANGDURIGE BLOOTSTELLING/CONTACT:

- Droge huid
- Gebarsten huid

11.5 Chronische effecten:

NA LANGDURIGE/HERHAALDE BLOOTSTELLING/CONTACT:

- Rode huid
- Huiduitslag/ontsteking
- Droge keel/keelpijn
- Hoofdpijn
- Misselijkheid
- Zwaktegevoel
- Gewichtsverlies
- Kans op ontsteking van de luchtwegen

12. Milieu-informatie

12.1 Ecotoxiciteit:

ACETON:

- LC50 (96 u) : 5540 mg/l (SALMO GAIIRDNERI/ONCORHYNCHUS MYKISS)
- EC50 (48 u) : 39 mg/l (DAPHNIA MAGNA)
- EC50 (96 u) : 7000 mg/l (SELENASTRUM CAPRICORNUTUM)

12.2 Mobiliteit:

- Vluchtige organische stoffen (VOS): 100 %

Voor andere fysico-chemische eigenschappen zie rubriek 9

12.3 Persistentie en afbraak:

- biodegradatie BOD₅ : N.B. % ThOD
- water : Geen gegevens beschikbaar
- bodem : T ½ N.B. dagen

12.4 Mogelijke bioaccumulatie:

- log P_{ow} : N.B.
- BCF : N.B.

12.5 Andere schadelijke effecten:

- WGK : 1 (Classificatie op basis van de componenten volgens Verwaltungsverfahren wassergefährdender Stoffe (VwVwS) van 17 mei 1999)
- Effect op de ozonlaag : Niet gevaarlijk voor de ozonlaag (1999/45/EG)
- Broeikaseffect : Geen gegevens beschikbaar
- Effect op de afvalwaterzuivering : Geen gegevens beschikbaar

13. Instructies voor verwijdering

13.1 Afvalvoorschriften:

- Afvalstofcode (91/689/EEG, Beschikking 2001/118/EG van de Commissie, P.B. L47 van 16/2/2001): 07 01 04 (overige organische oplosmiddelen, wasvloeistoffen en moederlogen)
- Gevaarlijk afval (91/689/EEG)


13.2 Verwijderingsmethoden:

- Specifieke verwerking

13.3 Verpakking:

- Afvalstofcode verpakking (91/689/EEG, Beschikking 2001/118/EG van de Commissie, P.B. L47 van 16/2/2001): 15 01 10* (verpakking die resten van gevaarlijke stoffen bevat of daarmee is verontreinigd)

14. Informatie met betrekking tot het vervoer



- 14.1 Indeling van de stof overeenkomstig de UNO-aanbevelingen
- | | | |
|----------------------|---|----------------------|
| UNO-nummer | : | 1950 |
| KLASSE | : | 2.1 |
| SUB RISKS | : | - |
| VERPAKKINGSGROEP | : | - |
| PROPER SHIPPING NAME | : | UN 1950, Spuitbussen |
- 14.2 ADR (vervoer over de weg)
- | | | |
|-------------------|---|-----|
| KLASSE | : | 2 |
| CLASSIFICATIECODE | : | 5 F |
| ETIKET TANKS | : | - |
| ETIKET COLLI | : | 2.1 |
- 14.3 RID (vervoer per spoor)
- | | | |
|-------------------|---|-----|
| KLASSE | : | 2 |
| CLASSIFICATIECODE | : | 5 F |
| ETIKET TANKS | : | - |
| ETIKET COLLI | : | 2.1 |
- 14.4 ADNR (vervoer over de binnenwateren)
- | | | |
|-------------------|---|-----|
| KLASSE | : | 2 |
| CLASSIFICATIECODE | : | 5 F |
| ETIKET TANKS | : | - |
| ETIKET COLLI | : | 2.1 |
- 14.5 IMDG (vervoer over zee)
- | | | |
|------------------|---|----------|
| KLASSE | : | 2.1 |
| SUB RISKS | : | - |
| VERPAKKINGSGROEP | : | - |
| MFAG | : | - |
| EMS | : | F-D, S-U |
| MARINE POLLUTANT | : | - |
- 14.6 ICAO (vervoer over de lucht)
- | | | |
|---|---|----------|
| KLASSE | : | 2.1 |
| SUB RISKS | : | - |
| VERPAKKINGSGROEP | : | - |
| VERPAKKINGSINSTRUCTIES PASSENGER AIRCRAFT | : | 203/Y203 |
| VERPAKKINGSINSTRUCTIES CARGO AIRCRAFT | : | 203 |
- 14.7 Speciale voorzorgsmaatregelen met betrekking tot het vervoer
- | | | |
|--|---|------|
| | : | Geen |
|--|---|------|
- 14.8 Limited quantities (LQ)
- | | | |
|--|---|--|
| | : | |
|--|---|--|

Indien de stoffen en hun verpakkingen beantwoorden aan hoofdstuk 3.4 van het ADR/RID/ADNR moeten **alleen** de volgende verplichtingen nageleefd worden:
op elke verpakking moet een ruit worden aangebracht met daarin de vermelding:
- 'UN 1950'
of, indien meerdere stoffen met verschillende identificatienummers in één en hetzelfde collo verpakt zijn:
- de letters 'LQ'

15. Wettelijk verplichte informatie

Etikettering volgens richtlijnen 67/548/EEG en 1999/45/EG



Zeer licht ontvlambaar



Irriterend

- R36 : Irriterend voor de ogen
R66 : Herhaalde blootstelling kan een droge of een gebarsten huid veroorzaken
R67 : Dampen kunnen slaperigheid en duizeligheid veroorzaken
- S(02) : (Buiten bereik van kinderen bewaren)
S09 : Op een goed geventileerde plaats bewaren
S16 : Verwijderd houden van ontstekingsbronnen - niet roken
S26 : Bij aanraking met de ogen onmiddellijk met overvloedig water afspoelen en deskundig medisch advies inwinnen

Verwijderd houden van ontstekingsbronnen - niet roken
Buiten bereik van kinderen bewaren
Houder onder druk. Te beschermen tegen zonnestralen en niet blootstellen aan temperaturen hoger dan 50°C.
Ook na gebruik niet doorboren of verbranden
Niet verstuiven naar een vlam of een verhit voorwerp

16. Overige informatie

De informatie in dit veiligheidsblad werd opgesteld naar best vermogen, en geeft de stand van kennis weer op het ogenblik van publicatie. De gegevens zijn weergegeven als richtlijn voor het veilig hanteren, gebruik, verbruik, opslag, vervoer, verwijdering van de stof, en kunnen niet worden beschouwd als waarborg of kwaliteitsspecificatie. De vermelde gegevens hebben betrekking op de stof als dusdanig, en zijn mogelijk niet meer geldig wanneer de stof wordt gebruikt samen met andere stoffen, of in processen, tenzij aangegeven in de tekst.

N.A. = NIET VAN TOEPASSING
N.B. = NIET BEPAALD
***** = INTERNE CLASSIFICATIE

Volledige tekst van alle R-zinnen vermeld onder rubriek 2:

R11 : Licht ontvlambaar
R12 : Zeer licht ontvlambaar
R36 : Irriterend voor de ogen
R66 : Herhaalde blootstelling kan een droge of een gebarsten huid veroorzaken
R67 : Dampen kunnen slaperigheid en duizeligheid veroorzaken

Blootstellingsnormen:

TLV : Threshold Limit Value - ACGIH US 2002
OES : Occupational Exposure Standards - Verenigd Koninkrijk 1999
MEL : Maximum Exposure Limits - Verenigd Koninkrijk 1999
MAK : Maximale Arbeitsplatzkonzentrationen - Duitsland 2001
TRK : Technische Richtkonzentrationen - Duitsland 2001
MAC : Maximale aanvaarde concentratie - Nederland 2002
VME : Valeurs limites de Moyenne d'Exposition - Frankrijk 1999
VLE : Valeurs limites d'Exposition à court terme - Frankrijk 1999
GWBB : Grenswaarde beroepsmatige blootstelling - België 2002
GWK : Grenswaarde kortstondige blootstelling - België 2002
EG : Indicatieve grenswaarden voor beroepsmatige blootstelling - richtlijn 2000/39/EG

I : Inhaleerbare fractie = **T** : Totaal stof = **E** : Einatembare Aerosolanteil
R : Inadembare fractie = **A** : Alveolengängiger Aerosolanteil/Alveolair stof
C : Ceiling limit

a:	aërosol	r:	rook
d:	damp	st:	stof
du:	dust (stof)	ve:	vezel
fa:	Faser (vezel)	va:	vapour (damp)
fi:	fibre (vezel)	om:	oil mist (olienevel)
fu:	fume (rook)	on:	olienevel
p:	poussière (stof)	part:	particles (stofdeeltjes)

Chronische toxiciteit:

K : Lijst van de kankerverwekkende stoffen en processen - Nederland 2002

Soudafoam 2K**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1 Product identifier:**

Product name : Soudafoam 2K
Product type REACH : Mixture

1.2 Relevant identified uses of the substance or mixture and uses advised against:**1.2.1 Relevant identified uses**

Adhesive
Sealing compound
polyurethane

1.2.2 Uses advised against

No uses advised against known

1.3 Details of the supplier of the safety data sheet:**Supplier of the safety data sheet**

SOUDAL N.V.
Everdongenlaan 18-20
B-2300 Turnhout
☎ +32 14 42 42 31
☐ +32 14 42 65 14
msds@soudal.com

Manufacturer of the product

SOUDAL N.V.
Everdongenlaan 18-20
B-2300 Turnhout
☎ +32 14 42 42 31
☐ +32 14 42 65 14
msds@soudal.com

1.4 Emergency telephone number:

24h/24h (Telephone advice: English, French, German, Dutch):
+32 14 58 45 45 (BIG)

SECTION 2: Hazards identification**2.1 Classification of the substance or mixture:****2.1.1 Classification according to Regulation EC No 1272/2008**

Classified as dangerous according to the criteria of Regulation (EC) No 1272/2008

Class	Category	Hazard statements
Aerosol	category 1	H222: Extremely flammable aerosol.
Aerosol	category 1	H229: Pressurised container: May burst if heated.
Acute Tox.	category 4	H332: Harmful if inhaled.
STOT RE	category 2	H373: May cause damage to organs through prolonged or repeated exposure if inhaled.
Eye Irrit.	category 2	H319: Causes serious eye irritation.
STOT SE	category 3	H335: May cause respiratory irritation.
Skin Irrit.	category 2	H315: Causes skin irritation.
Resp. Sens.	category 1	H334: May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Skin Sens.	category 1	H317: May cause an allergic skin reaction.
Carc.	category 2	H351: Suspected of causing cancer.

2.1.2 Classification according to Directive 67/548/EEC-1999/45/EC

Classified as dangerous in accordance with the criteria of Directives 67/548/EEC and 1999/45/EC

Carc. Cat. 3; R40 - Limited evidence of a carcinogenic effect

F+; R12 - Extremely flammable.

Xn; R20 - 48/20 - Harmful by inhalation. Harmful: danger of serious damage to health by prolonged exposure through inhalation.

Xi; R36/37/38 - Irritating to eyes, respiratory system and skin.

Soudafoam 2K

R42/43 - May cause sensitisation by inhalation and skin contact.

2.2 Label elements:

Labelling according to Regulation EC No 1272/2008 (CLP)

Drawn up according to the criteria of Regulation (EU) No 487/2013, 4th adaptation of Regulation (EC) No 1272/2008



Contains: polymethylene polyphenyl isocyanate.

Signal word

Danger

H-statements

H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
H351	Suspected of causing cancer.
H332	Harmful if inhaled.
H373	May cause damage to organs through prolonged or repeated exposure if inhaled.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H315	Causes skin irritation.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H317	May cause an allergic skin reaction.

P-statements

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P362 + P364	Take off contaminated clothing and wash it before reuse.
P410 + P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122°F.
P501	Dispose of contents/container in accordance with local/regional/national/international regulation.

Supplemental information

- Persons already sensitised to diisocyanates may develop allergic reactions when using this product.
- Persons suffering from asthma, eczema or skin problems should avoid contact, including dermal contact, with this product.
- This product should not be used under conditions of poor ventilation unless a protective mask with an appropriate gas filter (i.e. type A1 according to standard EN 14387) is used.

Labelling according to Directive 67/548/EEC-1999/45/EC (DSD/DPD)

Labels



Extremely flammable



Harmful

Contains: polymethylene polyphenyl isocyanate.

R-phrases

20	Harmful by inhalation
36/37/38	Irritating to eyes, respiratory system and skin
40	Limited evidence of a carcinogenic effect
42/43	May cause sensitisation by inhalation and skin contact
48/20	Harmful: danger of serious damage to health by prolonged exposure through inhalation

S-phrases

02	Keep out of the reach of children
16	Keep away from sources of ignition - No smoking
23	Do not breathe spray
36/37	Wear suitable protective clothing and gloves
45	In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible)
51	Use only in well-ventilated areas
(63)	(In case of accident by inhalation: remove casualty to fresh air and keep at rest)

Additional recommendations

- Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C.
- Do not pierce or burn, even after use.

Reason for revision: 2.2

Publication date: 2005-04-27

Date of revision: 2014-08-29

Revision number: 0600

Product number: 42122

2 / 15

Soudafoam 2K

Do not spray on a naked flame or any incandescent material.

Contains isocyanates. See information supplied by the manufacturer.

- Persons already sensitised to diisocyanates may develop allergic reactions when using this product.

- Persons suffering from asthma, eczema or skin problems should avoid contact, including dermal contact, with this product.

- This product should not be used under conditions of poor ventilation unless a protective mask with an appropriate gas filter (i.e. type A1 according to standard EN 14387) is used.

2.3 Other hazards:

CLP

May be ignited by sparks

Gas/vapour spreads at floor level: ignition hazard

Aerosol may explode under the effect of heat

DSD/DPD

May be ignited by sparks

Gas/vapour spreads at floor level: ignition hazard

Aerosol may explode under the effect of heat

SECTION 3: Composition/information on ingredients

3.1 Substances:

Not applicable

3.2 Mixtures:

Name REACH Registration No	CAS No EC No	Conc. (C)	Classification according to DSD/DPD	Classification according to CLP	Note	Remark
tris(2-chloro-1-methylethyl) phosphate 01-2119447716-31	13674-84-5 237-158-7	1%<C<25%	Xn; R22	Acute Tox. 4; H302	(1)(10)	Constituent
polymethylene polyphenyl isocyanate	9016-87-9	C>25 %	Carc. Cat. 3; R40 Xn; R20 - 48/20 Xi; R36/37/38 R42/43	Carc. 2; H351 Acute Tox. 4; H332 STOT RE 2; H373 Eye Irrit. 2; H319 STOT SE 3; H335 Skin Irrit. 2; H315 Resp. Sens. 1; H334 Skin Sens. 1; H317	(1)(2)(10)	Polymer
propane 01-2119486944-21	74-98-6 200-827-9	1%<C<10%	F+; R12	Flam. Gas 1; H220 Press. Gas - Liquefied gas; H280	(1)(2)(10)	Propellant
isobutane 01-2119485395-27	75-28-5 200-857-2	1%<C<10%	F+; R12	Flam. Gas 1; H220 Press. Gas - Liquefied gas; H280	(1)(2)(10)	Propellant
dimethyl ether 01-2119472128-37	115-10-6 204-065-8	1%<C<10%	F+; R12	Flam. Gas 1; H220 Press. Gas - Liquefied gas; H280	(1)(2)(10)	Propellant
(1,3-butadiene, conc<0.1%)						

(1) For R-phrases and H-statements in full: see heading 16

(2) Substance with a Community workplace exposure limit

(10) Subject to restrictions of Annex XVII of Regulation (EC) No. 1907/2006

SECTION 4: First aid measures

4.1 Description of first aid measures:

General:

If you feel unwell, seek medical advice.

After inhalation:

Remove the victim into fresh air. Respiratory problems: consult a doctor/medical service.

After skin contact:

Wash immediately with lots of water. Take victim to a doctor if irritation persists.

After eye contact:

Rinse immediately with plenty of water. Do not apply neutralizing agents. Take victim to an ophthalmologist if irritation persists.

After ingestion:

Rinse mouth with water. Immediately after ingestion: give lots of water to drink. Do not induce vomiting. Consult a doctor/medical service if you feel unwell.

Reason for revision: 2.2

Publication date: 2005-04-27

Date of revision: 2014-08-29

Revision number: 0600

Product number: 42122

3 / 15

Soudafoam 2K

4.2 Most important symptoms and effects, both acute and delayed:

4.2.1 Acute symptoms

After inhalation:

Dry/sore throat. Coughing. Irritation of the respiratory tract. Irritation of the nasal mucous membranes. Runny nose. FOLLOWING SYMPTOMS MAY APPEAR LATER: Possible inflammation of the respiratory tract. Risk of lung oedema. Respiratory difficulties.

After skin contact:

Tingling/irritation of the skin.

After eye contact:

Irritation of the eye tissue. Lacrimation.

After ingestion:

Not applicable.

4.2.2 Delayed symptoms

No effects known.

4.3 Indication of any immediate medical attention and special treatment needed:

If applicable and available it will be listed below.

SECTION 5: Firefighting measures

5.1 Extinguishing media:

5.1.1 Suitable extinguishing media:

Polyvalent foam. Water spray. BC powder. Carbon dioxide.

5.1.2 Unsuitable extinguishing media:

No unsuitable extinguishing media known.

5.2 Special hazards arising from the substance or mixture:

On burning: release of toxic and corrosive gases/vapours (phosphorus oxides, nitrous vapours, hydrogen chloride, carbon monoxide - carbon dioxide). May polymerize on exposure to temperature rise. On heating: release of toxic/combustible gases/vapours (hydrogen cyanide).

5.3 Advice for firefighters:

5.3.1 Instructions:

If exposed to fire cool the closed containers by spraying with water. Physical explosion risk: extinguish/cool from behind cover. Do not move the load if exposed to heat. After cooling: persistent risk of physical explosion. Dilute toxic gases with water spray.

5.3.2 Special protective equipment for fire-fighters:

Gloves. Protective goggles. Head/neck protection. Protective clothing. Heat/fire exposure: compressed air/oxygen apparatus.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures:

Stop engines and no smoking. No naked flames or sparks. Spark- and explosionproof appliances and lighting equipment.

6.1.1 Protective equipment for non-emergency personnel

See heading 8.2

6.1.2 Protective equipment for emergency responders

Gloves. Protective goggles. Head/neck protection. Protective clothing.

Suitable protective clothing

See heading 8.2

6.2 Environmental precautions:

Dam up the solid spill. Use appropriate containment to avoid environmental contamination.

6.3 Methods and material for containment and cleaning up:

Allow product to solidify and remove it by mechanical means. Clean (treat) contaminated surfaces with acetone. Take collected spill to manufacturer/competent authority. Wash clothing and equipment after handling.

6.4 Reference to other sections:

See heading 13.

SECTION 7: Handling and storage

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

7.1 Precautions for safe handling:

Use spark-/explosionproof appliances and lighting system. Keep away from naked flames/heat. Keep away from ignition sources/sparks. Gas/vapour heavier than air at 20°C. Observe very strict hygiene - avoid contact. Remove contaminated clothing immediately.

7.2 Conditions for safe storage, including any incompatibilities:

Reason for revision: 2.2

Publication date: 2005-04-27

Date of revision: 2014-08-29

Revision number: 0600

Product number: 42122

4 / 15

Soudafoam 2K

7.2.1 Safe storage requirements:

Storage temperature: < 50 °C. Store in a cool area. Keep out of direct sunlight. Ventilation at floor level. Fireproof storeroom. Unauthorized persons are not admitted. Meet the legal requirements. Max. storage time: 1 year(s).

7.2.2 Keep away from:

Heat sources, ignition sources, (strong) acids, (strong) bases, amines.

7.2.3 Suitable packaging material:

Aerosol.

7.2.4 Non suitable packaging material:

No data available

7.3 Specific end use(s):

If applicable and available, exposure scenarios are attached in annex. See information supplied by the manufacturer.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters:

8.1.1 Occupational exposure

a) Occupational exposure limit values

If limit values are applicable and available these will be listed below.

The Netherlands

Dimethylether	Time-weighted average exposure limit 8 h	496 ppm	Public occupational exposure limit value
	Time-weighted average exposure limit 8 h	950 mg/m ³	Public occupational exposure limit value
	Short time value	783 ppm	Public occupational exposure limit value
	Short time value	1500 mg/m ³	Public occupational exposure limit value

EU

Dimethylether	Time-weighted average exposure limit 8 h	1000 ppm	Indicative occupational exposure limit value
	Time-weighted average exposure limit 8 h	1920 mg/m ³	Indicative occupational exposure limit value

Belgium

Hydrocarbures aliphatiques sous forme gazeuse : (Alcanes C1-C4)	Time-weighted average exposure limit 8 h	1000 ppm	
Oxyde de diméthyle	Time-weighted average exposure limit 8 h	1000 ppm	
	Time-weighted average exposure limit 8 h	1920 mg/m ³	

USA (TLV-ACGIH)

Butane, all isomers	Time-weighted average exposure limit 8 h	1000 ppm	TLV - Adopted Value
---------------------	--	----------	---------------------

Germany

Dimethylether	Time-weighted average exposure limit 8 h	1000 ppm	TRGS 900
	Time-weighted average exposure limit 8 h	1900 mg/m ³	TRGS 900
Isobutan	Time-weighted average exposure limit 8 h	1000 ppm	TRGS 900
	Time-weighted average exposure limit 8 h	2400 mg/m ³	TRGS 900
pMDI (als MDI berechnet)	Time-weighted average exposure limit 8 h	0.05 mg/m ³	TRGS 900
Propan	Time-weighted average exposure limit 8 h	1000 ppm	TRGS 900
	Time-weighted average exposure limit 8 h	1800 mg/m ³	TRGS 900

France

Oxyde de diméthyle	Time-weighted average exposure limit 8 h	1000 ppm	VRI: Valeur réglementaire indicative
	Time-weighted average exposure limit 8 h	1920 mg/m ³	VRI: Valeur réglementaire indicative

UK

Dimethyl ether	Time-weighted average exposure limit 8 h	400 ppm	Workplace exposure limit (EH40/2005)
	Time-weighted average exposure limit 8 h	766 mg/m ³	Workplace exposure limit (EH40/2005)
	Short time value	500 ppm	Workplace exposure limit (EH40/2005)
	Short time value	958 mg/m ³	Workplace exposure limit (EH40/2005)
Isocyanates, all (as -NCO) Except methyl isocyanate	Time-weighted average exposure limit 8 h	0.02 mg/m ³	Workplace exposure limit (EH40/2005)
	Short time value	0.07 mg/m ³	Workplace exposure limit (EH40/2005)

b) National biological limit values

Reason for revision: 2.2

Publication date: 2005-04-27

Date of revision: 2014-08-29

Revision number: 0600

Product number: 42122

5 / 15

Soudafoam 2K

If limit values are applicable and available these will be listed below.

8.1.2 Sampling methods

Product name	Test	Number
1,2-ethanediol	NIOSH	5500
Ethylene Glycol	NIOSH	5523

8.1.3 Applicable limit values when using the substance or mixture as intended

If limit values are applicable and available these will be listed below.

8.1.4 DNEL/PNEC values

DNEL - Workers

tris(2-chloro-1-methylethyl) phosphate

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Acute systemic effects dermal	0.528 mg/kg bw/day	
	Acute systemic effects inhalation	0.93 mg/m ³	
	Long-term systemic effects dermal	0.528 mg/kg bw/day	
	Long-term systemic effects inhalation	0.93 mg/m ³	

DNEL - General population

tris(2-chloro-1-methylethyl) phosphate

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Acute systemic effects dermal	0.264 mg/kg bw/day	
	Acute systemic effects inhalation	0.23 mg/m ³	
	Acute -systemic effects oral	0.33 mg/kg bw/day	
	Long-term systemic effects dermal	0.264 mg/kg bw/day	
	Long-term systemic effects inhalation	0.23 mg/m ³	
	Long-term systemic effects oral	0.33 mg/kg bw/day	

8.1.5 Control banding

If applicable and available it will be listed below.

8.2 Exposure controls:

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

8.2.1 Appropriate engineering controls

Use spark-/explosionproof appliances and lighting system. Keep away from naked flames/heat. Keep away from ignition sources/sparks. Measure the concentration in the air regularly.

8.2.2 Individual protection measures, such as personal protective equipment

Observe very strict hygiene - avoid contact. Do not eat, drink or smoke during work.

a) Respiratory protection:

Wear gas mask with filter type A if conc. in air > exposure limit.

b) Hand protection:

Gloves.

Materials	Breakthrough time	Thickness
LDPE (Low Density Poly Ethylene)	10 minutes	0.025 mm

- materials (good resistance)

LDPE (Low Density Poly Ethylene).

c) Eye protection:

Protective goggles.

d) Skin protection:

Head/neck protection. Protective clothing.

8.2.3 Environmental exposure controls:

See headings 6.2, 6.3 and 13

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties:

Physical form	Aerosol
Odour	Characteristic odour
Odour threshold	No data available
Colour	Variable in colour, depending on the composition
Particle size	No data available
Explosion limits	No data available
Flammability	Extremely flammable aerosol.
Log Kow	Not applicable (mixture)
Dynamic viscosity	No data available

Reason for revision: 2.2

Publication date: 2005-04-27

Date of revision: 2014-08-29

Revision number: 0600

Product number: 42122

6 / 15

Soudafoam 2K

Kinematic viscosity	No data available
Melting point	No data available
Boiling point	No data available
Flash point	No data available
Evaporation rate	No data available
Relative vapour density	> 1
Vapour pressure	No data available
Solubility	water ; insoluble organic solvents ; soluble
Relative density	No data available
Decomposition temperature	No data available
Auto-ignition temperature	No data available
Explosive properties	No chemical group associated with explosive properties
Oxidising properties	No chemical group associated with oxidising properties
pH	No data available

Physical hazards

Flammable liquid

9.2 Other information:

Surface tension	No data available
Absolute density	No data available

SECTION 10: Stability and reactivity

10.1 Reactivity:

May be ignited by sparks. Gas/vapour spreads at floor level: ignition hazard. No data available.

10.2 Chemical stability:

Stable under normal conditions.

10.3 Possibility of hazardous reactions:

May polymerize with many compounds e.g.: (strong) bases and amines. Reacts violently with (some) acids/bases.

10.4 Conditions to avoid:

Use spark-/explosionproof appliances and lighting system. Keep away from naked flames/heat. Keep away from ignition sources/sparks.

10.5 Incompatible materials:

(strong) acids, (strong) bases, amines.

10.6 Hazardous decomposition products:

On heating: release of toxic/combustible gases/vapours (hydrogen cyanide). On burning: release of toxic and corrosive gases/vapours (phosphorus oxides, nitrous vapours, hydrogen bromide, hydrogen chloride, carbon monoxide - carbon dioxide).

SECTION 11: Toxicological information

11.1 Information on toxicological effects:

11.1.1 Test results

Acute toxicity

Soudafoam 2K

No (test)data on the mixture available

tris(2-chloro-1-methylethyl) phosphate

Route of exposure	Parameter	Method	Value	Exposure time	Species	Gender	Value determination
Oral	LD50	Equivalent to OECD 401	1011-1824 mg/kg bw		Rat	Male/female	Experimental value
Dermal	LD50	OECD 402	> 2000 mg/kg bw	24 h	Rabbit	Male/female	Experimental value
Inhalation (aerosol)	LC50	Equivalent to OECD 403	> 5 mg/l air	4 h	Rat	Male/female	Weight of evidence

polymethylene polyphenyl isocyanate

Route of exposure	Parameter	Method	Value	Exposure time	Species	Gender	Value determination
Oral	LD50		> 10000 mg/kg		Rat		Literature study
Dermal	LD50		> 5000 mg/kg		Rabbit		Literature study
Inhalation (vapours)	LD50		10-20 mg/l	4 h	Rat		Literature study

Reason for revision: 2.2

Publication date: 2005-04-27

Date of revision: 2014-08-29

Revision number: 0600

Product number: 42122

7 / 15

Soudafoam 2K

Classification is based on the relevant ingredients

Conclusion

Harmful if inhaled.

Corrosion/irritation

Soudafoam 2K

No (test)data on the mixture available

tris(2-chloro-1-methylethyl) phosphate

Route of exposure	Result	Method	Exposure time	Time point	Species	Value determination
Eye	Not irritating	Equivalent to OECD 405	72 h	24; 48; 72 hours	Rabbit	Experimental value
Skin	Not irritating	OECD 404	4 h		Rabbit	Experimental value

polymethylene polyphenyl isocyanate

Route of exposure	Result	Method	Exposure time	Time point	Species	Value determination
Eye	Irritating					Literature study
Skin	Irritating					Literature study
Inhalation	Irritating					Literature study

Classification is based on the relevant ingredients

Conclusion

Causes skin irritation.

Causes serious eye irritation.

May cause respiratory irritation.

Specific target organ toxicity, single exposure: classified as irritant to respiratory organs

Respiratory or skin sensitisation

Soudafoam 2K

No (test)data on the mixture available

tris(2-chloro-1-methylethyl) phosphate

Route of exposure	Result	Method	Exposure time	Observation time point	Species	Gender	Value determination
Skin	Not sensitizing	OECD 429			Mouse		Experimental value

polymethylene polyphenyl isocyanate

Route of exposure	Result	Method	Exposure time	Observation time point	Species	Gender	Value determination
Skin	Sensitizing						Literature study
Inhalation	Sensitizing						Literature study

Classification is based on the relevant ingredients

Conclusion

May cause an allergic skin reaction.

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Specific target organ toxicity

Soudafoam 2K

No (test)data on the mixture available

tris(2-chloro-1-methylethyl) phosphate

Route of exposure	Parameter	Method	Value	Organ	Effect	Exposure time	Species	Gender	Value determination
Oral	LOAEL	Equivalent to OECD 408	800 ppm	Liver	Weight gain	13 weeks (daily)	Rat	Male	Experimental value
Oral	NOAEL	Equivalent to OECD 408	2500 ppm		No effect	13 weeks (daily)	Rat	Female	Experimental value

polymethylene polyphenyl isocyanate

Route of exposure	Parameter	Method	Value	Organ	Effect	Exposure time	Species	Gender	Value determination
Inhalation			STOT RE cat.2						Literature study

Classification is based on the relevant ingredients

Conclusion

May cause damage to organs through prolonged or repeated exposure if inhaled.

Low sub-chronic toxicity by the oral route

Low sub-chronic toxicity by the dermal route

Mutagenicity (in vitro)

Reason for revision: 2.2

Publication date: 2005-04-27

Date of revision: 2014-08-29

Revision number: 0600

Product number: 42122

8 / 15

Soudafoam 2K

Soudafoam 2K

No (test)data on the mixture available

tris(2-chloro-1-methylethyl) phosphate

Result	Method	Test substrate	Effect	Value determination
Negative		Chinese hamster lung fibroblasts	No effect	Weight of evidence
Negative	Equivalent to OECD 471	Bacteria (S.typhimurium)	No effect	Weight of evidence
Negative	Equivalent to OECD 476	Mouse (lymphoma L5178Y cells)	No effect	Weight of evidence

Mutagenicity (in vivo)

Soudafoam 2K

No (test)data on the mixture available

tris(2-chloro-1-methylethyl) phosphate

Result	Method	Exposure time	Test substrate	Gender	Organ	Value determination
Negative	Equivalent to OECD 475		Rat	Male		Weight of evidence

Carcinogenicity

Soudafoam 2K

No (test)data on the mixture available

polymethylene polyphenyl isocyanate

Route of exposure	Parameter	Method	Value	Exposure time	Species	Gender	Value determination	Organ	Effect
Inhalation (aerosol)			category 2		Rat		Literature study		Neoplastic effects

Reproductive toxicity

Soudafoam 2K

No (test)data on the mixture available

tris(2-chloro-1-methylethyl) phosphate

	Parameter	Method	Value	Exposure time	Species	Gender	Effect	Organ	Value determination
Developmental toxicity	LOAEL (P)	OECD 416	99 mg/kg bw	>10 weeks (daily)	Rat	Female	Body weight, organ weight, food consumption	Female reproductive organ	Experimental value
	NOAEL (P)	OECD 416	85 mg/kg bw	>10 weeks (daily)	Rat	Male	No effect		Experimental value
	NOAEL	Equivalent to OECD 414	1000 mg/kg bw	70 day(s)	Rat	Female	No effect		Experimental value

Classification is based on the relevant ingredients

Conclusion CMR

Suspected of causing cancer.

Not classified for reprotoxic or developmental toxicity

Not classified for mutagenic or genotoxic toxicity

Toxicity other effects

Soudafoam 2K

No (test)data on the mixture available

Chronic effects from short and long-term exposure

Soudafoam 2K

ON CONTINUOUS/REPEATED EXPOSURE/CONTACT: Feeling of weakness. Itching. Skin rash/inflammation. May stain the skin. Dry skin. Coughing. Possible inflammation of the respiratory tract. Respiratory difficulties.

SECTION 12: Ecological information

12.1 Toxicity:

Soudafoam 2K

No (test)data on the mixture available

Reason for revision: 2.2

Publication date: 2005-04-27

Date of revision: 2014-08-29

Revision number: 0600

Product number: 42122

9 / 15

Soudafoam 2K

tris(2-chloro-1-methylethyl) phosphate

	Parameter	Method	Value	Duration	Species	Test design	Fresh/salt water	Value determination
Acute toxicity fishes	LC50		56.2 mg/l	96 h	Brachydanio rerio	Static system	Fresh water	Experimental value; GLP
Acute toxicity invertebrates	EC50	OECD 202	65 - 335 mg/l	48 h	Daphnia magna			Experimental value; GLP
Toxicity algae and other aquatic plants	EC50	OECD 201	73 mg/l	96 h	Selenastrum capricornutum			Experimental value; Growth rate

polymethylene polyphenyl isocyanate

	Parameter	Method	Value	Duration	Species	Test design	Fresh/salt water	Value determination
Acute toxicity other aquatic organisms	LC50		>1000 mg/l	96 h				Literature study
Toxicity aquatic micro-organisms	EC50	OECD 209	>100 mg/l		Activated sludge			Literature study

Classification of the mixture is based on the relevant ingredients of the mixture

Conclusion

Not classified as dangerous for the environment according to the criteria of Directive 1999/45/EC

Not classified as dangerous for the environment according to the criteria of Regulation (EC) No 1272/2008

12.2 Persistence and degradability:

tris(2-chloro-1-methylethyl) phosphate

Biodegradation water

Method	Value	Duration	Value determination
OECD 301E: Modified OECD Screening Test	14 %	28 day(s)	Experimental value
OECD 301C: Modified MITI Test (I)	0 %	28 day(s)	Experimental value

polymethylene polyphenyl isocyanate

Biodegradation water

Method	Value	Duration	Value determination
OECD 302C: Inherent Biodegradability: Modified MITI Test (II)	< 60 %		Experimental value

Conclusion

Contains non readily biodegradable component(s)

12.3 Bioaccumulative potential:

Soudafoam 2K

Log Kow

Method	Remark	Value	Temperature	Value determination
	Not applicable (mixture)			

tris(2-chloro-1-methylethyl) phosphate

BCF fishes

Parameter	Method	Value	Duration	Species	Value determination
BCF		0.8 - 4.6		Cyprinus carpio	Experimental value

Log Kow

Method	Remark	Value	Temperature	Value determination
		2.59		Experimental value

polymethylene polyphenyl isocyanate

BCF fishes

Parameter	Method	Value	Duration	Species	Value determination
BCF		1		Pisces	Literature study

Log Kow

Method	Remark	Value	Temperature	Value determination
	No data available			

Conclusion

No straightforward conclusion can be drawn based upon the available numerical values

12.4 Mobility in soil:

No (test)data on mobility of the components available

12.5 Results of PBT and vPvB assessment:

Reason for revision: 2.2

Publication date: 2005-04-27

Date of revision: 2014-08-29

Revision number: 0600

Product number: 42122

10 / 15

Soudafoam 2K

Due to insufficient data no statement can be made whether the component(s) fulfil(s) the criteria of PBT and vPvB according to Annex XIII of Regulation (EC) No 1907/2006.

12.6 Other adverse effects:

Soudafoam 2K

Global warming potential (GWP)

None of the known components is included in the list of fluorinated greenhouse gases (Regulation (EC) No 842/2006)

Ozone-depleting potential (ODP)

Not classified as dangerous for the ozone layer (Regulation (EC) No 1005/2009)

SECTION 13: Disposal considerations

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

13.1 Waste treatment methods:

13.1.1 Provisions relating to waste

Waste material code (Directive 2008/98/EC, Decision 2000/0532/EC).

08 05 01* (wastes not otherwise specified in 08: waste isocyanates).

16 05 04* (gases in pressure containers and discarded chemicals: gases in pressure containers (including halons) containing dangerous substances).

Depending on branch of industry and production process, also other waste codes may be applicable. Hazardous waste according to Directive 2008/98/EC.

13.1.2 Disposal methods

Recycle/reuse. Specific treatment. Remove waste in accordance with local and/or national regulations. Hazardous waste shall not be mixed together with other waste. Different types of hazardous waste shall not be mixed together if this may entail a risk of pollution or create problems for the further management of the waste. Hazardous waste shall be managed responsibly. All entities that store, transport or handle hazardous waste shall take the necessary measures to prevent risks of pollution or damage to people or animals. Do not discharge into drains or the environment.

13.1.3 Packaging/Container

Waste material code packaging (Directive 2008/98/EC).

15 01 10* (packaging containing residues of or contaminated by dangerous substances).

SECTION 14: Transport information

Road (ADR)

14.1 UN number:

UN number	1950
-----------	------

14.2 UN proper shipping name:

Proper shipping name	Aerosols
----------------------	----------

14.3 Transport hazard class(es):

Hazard identification number	
Class	2
Classification code	5F

14.4 Packing group:

Packing group	
Labels	2.1

14.5 Environmental hazards:

Environmentally hazardous substance mark	no
--	----

14.6 Special precautions for user:

Special provisions	190
Special provisions	327
Special provisions	344
Special provisions	625
Limited quantities	Combination packagings: not more than 1 liter per inner packaging for liquids. A package shall not weigh more than 30 kg. (gross mass)

Rail (RID)

14.1 UN number:

UN number	1950
-----------	------

14.2 UN proper shipping name:

Proper shipping name	Aerosols
----------------------	----------

14.3 Transport hazard class(es):

Hazard identification number	23
Class	2
Classification code	5F

14.4 Packing group:

Packing group	
---------------	--

Reason for revision: 2.2

Publication date: 2005-04-27

Date of revision: 2014-08-29

Revision number: 0600

Product number: 42122

11 / 15

Soudafoam 2K

Labels	2.1
14.5 Environmental hazards:	
Environmentally hazardous substance mark	no
14.6 Special precautions for user:	
Special provisions	190
Special provisions	327
Special provisions	344
Special provisions	625
Limited quantities	Combination packagings: not more than 1 liter per inner packaging for liquids. A package shall not weigh more than 30 kg. (gross mass)

Inland waterways (ADN)

14.1 UN number:	
UN number	1950
14.2 UN proper shipping name:	
Proper shipping name	Aerosols
14.3 Transport hazard class(es):	
Class	2
Classification code	5F
14.4 Packing group:	
Packing group	
Labels	2.1
14.5 Environmental hazards:	
Environmentally hazardous substance mark	no
14.6 Special precautions for user:	
Special provisions	190
Special provisions	327
Special provisions	344
Special provisions	625
Limited quantities	Combination packagings: not more than 1 liter per inner packaging for liquids. A package shall not weigh more than 30 kg. (gross mass)

Sea (IMDG/IMSBC)

14.1 UN number:	
UN number	1950
14.2 UN proper shipping name:	
Proper shipping name	Aerosols
14.3 Transport hazard class(es):	
Class	2.1
14.4 Packing group:	
Packing group	
Labels	2.1
14.5 Environmental hazards:	
Marine pollutant	-
Environmentally hazardous substance mark	no
14.6 Special precautions for user:	
Special provisions	63
Special provisions	190
Special provisions	277
Special provisions	327
Special provisions	344
Special provisions	959
Limited quantities	Combination packagings: not more than 1 liter per inner packaging for liquids. A package shall not weigh more than 30 kg. (gross mass)
14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code:	
Annex II of MARPOL 73/78	Not applicable

Air (ICAO-TI/IATA-DGR)

14.1 UN number:	
UN number	1950
14.2 UN proper shipping name:	
Proper shipping name	Aerosols, flammable
14.3 Transport hazard class(es):	

Reason for revision: 2.2

Publication date: 2005-04-27

Date of revision: 2014-08-29

Soudafoam 2K

Class	2.1
14.4 Packing group:	
Packing group	
Labels	2.1
14.5 Environmental hazards:	
Environmentally hazardous substance mark	no
14.6 Special precautions for user:	
Special provisions	A145
Special provisions	A167
Special provisions	A802
Passenger and cargo transport: limited quantities: maximum net quantity per packaging	30 kg G

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

European legislation:

VOC content Directive 2010/75/EU

VOC content	Remark
22 %	

REACH Annex XVII - Restriction

Contains component(s) subject to restrictions of Annex XVII of Regulation (EC) No 1907/2006: restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles.

	Designation of the substance, of the group of substances or of the mixture	Conditions of restriction
tris(2-chloro-1-methylethyl) phosphate polymethylene polyphenyl isocyanate	Liquid substances or mixtures which are regarded as dangerous in accordance with Directive 1999/45/EC or are fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: (a) hazard classes 2.1 to 2.4, 2.6 and 2.7, 2.8 types A and B, 2.9, 2.10, 2.12, 2.13 categories 1 and 2, 2.14 categories 1 and 2, 2.15 types A to F; (b) hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10; (c) hazard class 4.1; (d) hazard class 5.1.	1. Shall not be used in: — ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays, — tricks and jokes, — games for one or more participants, or any article intended to be used as such, even with ornamental aspects,2. Articles not complying with paragraph 1 shall not be placed on the market.3. Shall not be placed on the market if they contain a colouring agent, unless required for fiscal reasons, or perfume, or both, if they: — can be used as fuel in decorative oil lamps for supply to the general public, and, — present an aspiration hazard and are labelled with R65 or H304,4. Decorative oil lamps for supply to the general public shall not be placed on the market unless they conform to the European Standard on Decorative oil lamps (EN 14059) adopted by the European Committee for Standardisation (CEN).5. Without prejudice to the implementation of other Community provisions relating to the classification, packaging and labelling of dangerous substances and mixtures, suppliers shall ensure, before the placing on the market, that the following requirements are met: a) lamp oils, labelled with R65 or H304, intended for supply to the general public are visibly, legibly and indelibly marked as follows: "Keep lamps filled with this liquid out of the reach of children"; and, by 1 December 2010, "Just a sip of lamp oil — or even sucking the wick of lamps — may lead to life- threatening lung damage"; b) grill lighter fluids, labelled with R65 or H304, intended for supply to the general public are legibly and indelibly marked by 1 December 2010 as follows: "Just a sip of grill lighter may lead to life threatening lung damage"; c) lamp oils and grill lighters, labelled with R65 or H304, intended for supply to the general public are packaged in black opaque containers not exceeding 1 litre by 1 December 2010.6. No later than 1 June 2014, the Commission shall request the European Chemicals Agency to prepare a dossier, in accordance with Article 69 of the present Regulation with a view to ban, if appropriate, grill lighter fluids and fuel for decorative lamps, labelled R65 or H304, intended for supply to the general public.7. Natural or legal persons placing on the market for the first time lamp oils and grill lighter fluids, labelled with R65 or H304, shall by 1 December 2011, and annually thereafter, provide data on alternatives to lamp oils and grill lighter fluids labelled R65 or H304 to the competent authority in the Member State concerned. Member States shall make those data available to the Commission.'
polymethylene polyphenyl isocyanate	Methylenediphenyl diisocyanate (MDI) including the following specific isomers: 4,4'-Methylenediphenyl diisocyanate; 2,4'-Methylenediphenyl diisocyanate; 2,2'-Methylenediphenyl diisocyanate	1. Shall not be placed on the market after 27 December 2010, as a constituent of mixtures in concentrations equal to or greater than 0.1 % by weight of MDI for supply to the general public, unless suppliers shall ensure before the placing on the market that the packaging: (a) contains protective gloves which comply with the requirements of Council Directive 89/686/EEC; (b) is marked visibly, legibly and indelibly as follows, and without prejudice to other Community legislation concerning the classification, packaging and labelling of substances and mixtures: "— Persons already sensitised to diisocyanates may develop allergic reactions when using this product. "— Persons suffering from asthma, eczema or skin problems should avoid contact, including dermal contact, with this product. "— This product should not be used under conditions of poor ventilation unless a protective mask with an appropriate gas filter (i.e. type A1 according to standard EN 14387) is used.2. By way of derogation, paragraph 1(a) shall not apply to hot melt adhesives.

Reason for revision: 2.2

Publication date: 2005-04-27

Date of revision: 2014-08-29

Revision number: 0600

Product number: 42122

13 / 15

Soudafoam 2K

Reference legislation

See column 1: 3.

See column 1: 40.

See column 1: 56.

Recommendations REACH annex XVII

- Persons already sensitised to diisocyanates may develop allergic reactions when using this product.

National legislation The Netherlands

Soudafoam 2K

Waste identification (the Netherlands)	LWCA (the Netherlands): KGA category 06
Waterbezwaarlijkheid	11

National legislation Germany

Soudafoam 2K

WGK	1; Classification water polluting based on the components in compliance with Verwaltungsvorschrift wassergefährdender Stoffe (VwVwS) of 27 July 2005 (Anhang 4)
-----	---

polymethylene polyphenyl isocyanate

TRGS905 - Krebserzeugend	3
TRGS905 - Erbgutverändernd	-
TRGS905 - Fruchtbarkeitsgefährdend	-
TRGS905 - Fruchtschädigend	-
MAK - Krebserzeugend Kategorie	4
Schwangerschaft Gruppe	C
MAK 8-Stunden-Mittelwert mg/m ³	„polymeres MDI“ (eintembare Fraktion); 0.05 mg/m ³ ; gemessen als eintembare Fraktion (vgl. Abschn. Vd) S. 191)

National legislation France

Soudafoam 2K

No data available

National legislation Belgium

Soudafoam 2K

No data available

15.2 Chemical safety assessment:

No chemical safety assessment is required.

SECTION 16: Other information

Full text of any R-phrases referred to under headings 2 and 3:

R20 Harmful by inhalation
R22 Harmful if swallowed
R36/37/38 Irritating to eyes, respiratory system and skin
R40 Limited evidence of a carcinogenic effect
R42/43 May cause sensitisation by inhalation and skin contact
R48/20 Harmful: danger of serious damage to health by prolonged exposure through inhalation

Full text of any H-statements referred to under headings 2 and 3:

H220 Extremely flammable gas.
H222 Extremely flammable aerosol.
H229 Pressurised container: May burst if heated.
H280 Contains gas under pressure; may explode if heated.
H302 Harmful if swallowed.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H332 Harmful if inhaled.
H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335 May cause respiratory irritation.
H351 Suspected of causing cancer.
H373 May cause damage to organs through prolonged or repeated exposure if inhaled.

(*) = INTERNAL CLASSIFICATION BY BIG

PBT-substances = persistent, bioaccumulative and toxic substances

DSD Dangerous Substance Directive

DPD Dangerous Preparation Directive

CLP (EU-GHS) Classification, labelling and packaging (Globally Harmonised System in Europe)

Reason for revision: 2.2

Publication date: 2005-04-27

Date of revision: 2014-08-29

Revision number: 0600

Product number: 42122

14 / 15

Soudafoam 2K

The information in this safety data sheet is based on data and samples provided to BIG. The sheet was written to the best of our ability and according to the state of knowledge at that time. The safety data sheet only constitutes a guideline for the safe handling, use, consumption, storage, transport and disposal of the substances/preparations/mixtures mentioned under point 1. New safety data sheets are written from time to time. Only the most recent versions may be used. Old versions must be destroyed. Unless indicated otherwise word for word on the safety data sheet, the information does not apply to substances/preparations/mixtures in purer form, mixed with other substances or in processes. The safety data sheet offers no quality specification for the substances/preparations/mixtures in question. Compliance with the instructions in this safety data sheet does not release the user from the obligation to take all measures dictated by common sense, regulations and recommendations or which are necessary and/or useful based on the real applicable circumstances. BIG does not guarantee the accuracy or exhaustiveness of the information provided and cannot be held liable for any changes by third parties. This safety data sheet is only to be used within the European Union, Switzerland, Iceland, Norway and Liechtenstein. Any use outside of this area is at your own risk. Use of this safety data sheet is subject to the licence and liability limiting conditions as stated in your BIG licence agreement or when this is failing the general conditions of BIG. All intellectual property rights to this sheet are the property of BIG and its distribution and reproduction are limited. Consult the mentioned agreement/conditions for details.

Reason for revision: 2.2

Publication date: 2005-04-27

Date of revision: 2014-08-29

Revision number: 0600

Product number: 42122

15 / 15