

MOTIP Zinc Spray

Technical Information



Fast drying zinc spray with good filling properties and excellent adhesion for professional use. To treat galvanised and untreated steel. Zinc spray has outstanding cathodic corrosion prevention, is spot-weldable and is resistant to petrol, chemicals and weather influences. MOTIP Industrial Zinc Spray is heat resistant to 350°C.

Ord.-no: 07301

Quality & properties

- Fast drying
- Good filling property
- Outstanding cathodic corrosion prevention
- Resistant to petrol, chemicals and weather influences
- Spot-weldable
- Excellent adhesion
- 90% of zinc in dry film

Physical & chemical data

- Base: Nitrocombi resin
- Colourname: grey
- Smell: Characteristic
- Degree of gloss: mat, 10 ±2
- Efficiency: 500 ML – 1.5 - 2.0 m²
- Dust dry: 10 - 15 min
- Dry to touch: 20 - 30 min
- Completely dry: 24 h
- Overcoatable: 24 h
- Surfaces: galvanised and untreated steel
- Minimum Working Temperature: 10 °C
- Maximum Working Temperature: 25 °C
- Flash point: n.a.
- Temperature resistance: 350 °C
- Storage stability: 10 years
- Content: 500 ML

How to use

Before use, carefully read the directions on the packaging and act accordingly. The surface should be clean, dry and free of grease. Remove loose old lacquer and rust and sand the surface. The surface should be clean, dry and free of grease. The aerosol should have room temperature. Best processing temperature 15 to 25°C. Before use, shake the aerosol for 2 minutes and spray a sample. Distance to the surface to be treated approximately 25 to 30 centimetre. Apply the zinc spray in several thin layers. Before applying the next layer, again shake the aerosol. When desired, after drying a primer and a lacquer can be applied. After use, clean the valve (turn aerosol upside down and press the nozzle for approximately 5 seconds). The drying time depends on the ambient temperature, the humidity of the air and the thickness of the lacquer applied.

Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

As of August 4, 2025 – This release replaces all eventually earlier issued versions.